

BUREAU VERITAS
Certification



'S' Mark Licence

Awarded to

Hyne & Son Pty Limited

Glue-Laminated Timber Plant

Activity Street, Maryborough, QLD 4650
AUSTRALIA

Bureau Veritas grants the above organization the right to use the Product Certification 'S' Mark as shown below only in respect of the products described and detailed in the Schedule to this Licence and manufactured in accordance with the requirements of the Standard indicated below under an approved Quality Management System. The Licence is granted subject to the 'Bureau Veritas Conditions of Service' and the 'Rules governing the use of Product Certification Licences'.

STANDARD

AS/NZS 1328.1:1998

Glued laminated structural timber

Part 1: Performance requirements and minimum production requirements

Licence No: 2757

Date Granted: 1 June 2017

Expiry Date: 1 June 2022

Signed on behalf of Bureau Veritas

Sam Guindi
Product Certification Manager



This Licence and its associated Schedule remain the property of Bureau Veritas and must be returned if certification is terminated. The constant compliance with the certification requirements is confirmed by regular surveillance measures from Bureau Veritas. In the case of serious non-compliance the certification will be withdrawn and deleted from the Register.

To check the validity of this certificate please contact. Bureau Veritas Australia Pty Ltd

Issuing office: Bureau Veritas Pty Ltd, 3/435 Williamstown Road, Port Melbourne, Victoria, 3207





SCHEDULE TO PRODUCT CERTIFICATION LICENCE NO: 2757

LICENCE DETAILS

Scheme: 'S' Mark Product Certification

Licensee: Hyne & Son Pty Limited
Glue-Laminated Timber Plant

Address: Activity Street,
Maryborough, QLD 4650
AUSTRALIA



CONFORMANCE REQUIREMENTS

Standard: AS/NZS 1328.1: 1998, Glued laminated structural timber
Part 1: Performance requirements and minimum production requirements

Quality System: Product Certification Quality System Requirements (QSR)

CERTIFIED MODEL OR TYPE

PRODUCT DESCRIPTION

Glued laminated timber members for structural use.

SPECIES

Slash & Carribea Pine (includes untreated, H2 and H3 treated), Victorian Ash / Tasmanian Oak, Blackbutt, Spotted Gum, Forest Red Gum and Ironbark

DESIGN STRENGTH

LGL (Pine), GL13 (Pine), GL17 (Pine), GL18 and GL21 (Hardwood)

SERVICE CLASS

1 & 3

ADHESIVES

Resorcinol (Hexion R27 and R15 with associated hardeners)