

DriStud FRU 36 Fire Retardant Self Support / Heavy-Weight Synthetic Roof Underlay

Product Technical Statement: 106725



DriStud FRU 36 is a fire retardant, self support/heavy weight synthetic roofing underlay.

[View miproducts listing](#)



Level of assurance needed to demonstrate NZ Building Code Compliance

Supporting documentation should include technical information by manufacturer and either an independent assessment or reference to an industry-based scheme



DriStud FRU 36 confirms that this minimum level of assurance has been met or exceeded by the following:

CodeMark
[AQ-100915-CMNZ](#)



masterspec partner

Technical Statement

Scope of use

Scope

DriStud FRU 36 is a fire retardant synthetic roofing underlay that is intended for use on new and existing buildings in wind zones up to and including "Extra High", as defined in NZS 3604:2011.

New Zealand Building Code (NZBC)

The product will, if employed in accordance with the supplier's installation and maintenance requirements, assist with meeting the following provisions of the building code:

- **Clause B1 Structure:** Performance B1.3.1, B1.3.2, B1.3.3(a), B1.3.3(h)
- **Clause B2 Durability:** Performance B2.3.1(a), B2.3.2(b)
- **Clause C3 Fire affecting areas beyond the fire source:** Performance C3.4(c)
- **Clause E2 External moisture:** Performance E2.3.1, E2.3.2, E2.3.7(a), E2.3.7(b), E2.3.7(c)
- **Clause F2 Hazardous building materials:** Performance F2.3.1

Supporting Evidence

The product has and can make available the following additional evidence to support the above statements:



CodeMark
[AQ-100915-CMNZ](#)

Product Criteria

Design requirements

FRU 36 is a lighter grammage self-support roof underlay and can be used for both self-support and heavy weight applications. DriStud FRU 36 is designed to be used as an underlay beneath roof claddings to assist with the weather tightness of buildings. This product can also be used as a wall underlay.

Please refer to MRM Code of Practice for design guides for places where condensation risks are high, such as cold or high humidity areas, low pitched roofs such as skillion roofs and roof cavities with restricted air movement.

Installation requirements

DriStud roofing underlay install with all writing and imagery facing out and with as minimal a number of overlaps as possible. Where overlaps are unavoidable a lap of 150 mm minimum must be used.

DriStud FRU 36 must be fully supported by a corrosion resistant material when roof pitch is less than 10°. DriStud roofing underlays must be installed as described in paragraph 8.1.5, E2/AS1 and DriStud FRU 36 Installation Guide.

Please refer to www.dristud.co.nz for installation guide.

Maintenance requirements

Maintenance

DriStud roofing underlays do not require any maintenance but when exposed through removal of roof cladding, the underlays must be inspected and any damaged areas repaired or replaced.

Storage & Transportation

DriStud FRU 36 rolls must be stored in a clean, dry place and must be protected from damage and weather. DriStud FRU 36 must not be exposed to UV light for more than 7 days.

Company Contact Details

DRISPACE
Tomorrow's build, today



Company: DriSpace

Physical Address: 7 Fisher Crescent
Mount Wellington
AUCKLAND 1060

Postal Address: PO Box 132166
Sylvia Park
AUCKLAND

Fax: 64 09 2737762

Email: sales@drispace.co.nz

Website: www.drispace.co.nz

DriStud FRU 36 Fire Retardant Self Support / Heavy-Weight Synthetic Roof Underlay

Product Technical Statement: 106725



Warrantees

Warranty

TCL Hunt Ltd warrants that all DriStud roofing underlays will be free from manufacturing defects. Upon receiving of DriStud roofing underlays, it is recommended that a visual check is made. Where defects are observed, these must be replaced.

If installed in accordance with TCL Hunt installation requirements, TCL Hunt warrants that DriStud roofing underlays will comply with all relevant provisions of the NZ Building Code, provided that:

- the balance of the external wall is installed in accordance with the NZ Building Code, and,
- all necessary maintenance is undertaken in respect of the external wall system.

Please refer to DriStud website www.dristud.co.nz for more information on warranty and disclaimer.

Company Product Information

Quality Assurance



ISO 9001 (Quality Management)



Date last validated: **02 March 2018**



Date last updated: **02 March 2018**

Disclaimer: The Product Technical Statement (PTS) template is copyright to Construction Information Limited. However the content of this PTS is the responsibility of the product manufacturer/supplier. Refer to the miproducts Terms and Conditions