

# Roofing Industries Multidek 500 metal roofing

Product Technical Statement: 102842



Profile roofing/cladding with concealed clip fastening

[View miproducts listing](#)



## Level of assurance needed to demonstrate NZ Building Code Compliance


Supporting documentation should include technical information by manufacturer and either an independent assessment or reference to an industry-based scheme



Roofing Industries confirms that this minimum level of assurance has been met or exceeded by the following:

New Zealand Metal Roofing Manufacturers Association Inc (NZMRM)

[Code of Practice](#)



## Technical Statement

### Scope of use

Multidek® is a wall and roof cladding with a trough profile and concealed clip fixing for non-specifically designed timber framed buildings designed and constructed in accordance with B1/AS1, NZS3604 and E2/AS1, non-specifically designed steel framed buildings to NASH 3405, and specifically designed buildings in accordance with B1/VM1 and AS/NZS 1170.

When used as a roof cladding:

- Multidek® may be used with a minimum roof gradient of 3 degrees.

When used as a wall cladding:

- Specific design is required.

### New Zealand Building Code (NZBC)

The product will, if employed in accordance with the supplier's installation and maintenance requirements, assist with meeting the following provisions of the building code:

- **Clause B1 Structure:** Performance B1.3.1, B1.3.2, B1.3.3(a), B1.3.3(b), B1.3.3(c), B1.3.3(f), B1.3.3(g), B1.3.3(h), B1.3.4
- **Clause B2 Durability:** Performance B2.3.1(b), B2.3.2
- **Clause C3 Fire affecting areas beyond the fire source:** Performance C3.7, C3.7(a)
- **Clause E2 External moisture:** Performance E2.3.1, E2.3.2
- **Clause F2 Hazardous building materials:** Performance F2.3.1

### Notes

The product will, when installed using the details in the Multidek® Profile Technical Summary, meet the following provisions of the building code:

- Clause B1 Structure: Performance B1.3.1; B1.3.2; B1.3.3 for the relevant physical conditions of a) self-weight, b) imposed gravity loads arising from use, (c) temperature, (f) earthquake, g (snow) and h) wind; B1.3.4
- Clause B2 Durability: Performance B2.3.1(b); B2.3.2
- Clause C3 Fire Affecting Areas Beyond the Fire Source: Performance C3.7 Multidek® is non-combustible and contributes to C3.7a)
- Clause E2 External moisture: Performance E2.3.1, E2.3.2 Multidek® complies with E2/AS1 if the roof gradient is 3 degrees or greater.
- F2 Hazardous Building Material: Performance F2.3.1

### Evidence

The product meets the requirements set out in the following documents, or relevant parts of cited standards within the documents:

- Acceptable Solution for External Moisture E2/AS1
- Verification Method for Structure B1/VM1
- Acceptable Solution B1/AS1
- Verification Method C/VM2
- AS/NZS 2728: 2013
- NZ Metal Roof and Wall Cladding Code of Practice Version 2.2/2012 (MRM Code of Practice) [link to [www.mrm.org.nz](http://www.mrm.org.nz)]
- Tested for wind loads to AS4040.2: 1992 Methods of testing sheet roof and wall cladding Resistance to wind pressures for non-cyclone regions.

### Supporting Evidence

The product has and can make available the following additional evidence to support the above statements:

masterspec partner

### Company Contact Details



Company: Roofing Industries  
Physical Address: 5 John Glenn Avenue  
North Harbour  
AUCKLAND  
Postal Address: PO Box 302385  
North Harbour  
AUCKLAND  
Telephone: 64 09 4144585  
Fax: 64 09 4144586  
Email: [office@roof.co.nz](mailto:office@roof.co.nz)  
Website: [www.roof.co.nz](http://www.roof.co.nz)

# Roofing Industries Multidek 500 metal roofing

Product Technical Statement: 102842



New Zealand Metal Roofing Manufacturers Association Inc (NZMRM)

[Code of Practice](#)

## Use in Service History

Multidek® Profile Technical Summary

Test information available for our coil supplied by NZ Steel and Pacific Coilcoaters, and past history of in-service use of metal long run roof and wall cladding within New Zealand.

Test information available for our coil supplied by NZ Steel and Pacific Coilcoaters, and past history of in-service use of metal long run roof and wall cladding within New Zealand.

## Product Criteria

### Design requirements

For fixings and fixing patterns, refer to the Roofing Industries Multidek® Profile Technical Summary, which is to be read in connection with E2/AS1, and the NZ Metal Roof and Wall Cladding Code of Practice.

E2/AS1 states that the use of the manufacturers information may provide a more optimum spacing of fixings, and this is recommended by Roofing Industries.

For purlin sizes, spacing and fixing, refer to NZS 3604 for Timber Framed buildings and NASH 3405 for Steel Framed Houses.

The substrate and coating system must be as recommended by Colorsteel or Colorcote for the environmental conditions at the intended building location, and as specified in E2/AS1 Table 20.

### Installation requirements

Materials in contact with Multidek® must be compatible as specified in E2/AS1 Table 21.

### Maintenance requirements

Regular maintenance will extend the life of Multidek® and associated accessories.

Maintenance guides are available from Roofing Industries or can be downloaded from either NZ Steel or Pacific Coilcoaters website.

Guide to regular maintenance

- Inspect the roof, including fasteners, and repair any damage every 6 months.
- Wash areas not receiving regular rain washing with fresh water at least every 3 – 6 months.
- Remove debris from gutters every 3 - 6 months.
- Remove any noticeable buildup of salt deposits and/or other contaminants when identified.
- Please consult with your local distributor when considering over painting to ensure correct procedures are undertaken.

### Warrantees

[Colorcote Warranty](#)

[NZ Steel Warranty](#)

## Company Product Information

### Environmental

Colorsteel and Colorcote prepainted steel has been extensively tested and proven in some of New Zealand's most extreme UV, wind, rain, snow and ice environments.

All Colorsteel and Colorcote is factory painted at either NZ Steel, Glenbrook or Pacific Coilcoaters, Penrose. Both plants operate within strict environmental controls.

Environmental category literature available by request or the [roof.co.nz](http://roof.co.nz) website, or by contacting Roofing Industries, technical helpline 0800 844 822

### Relationships



New Zealand Made



Date last validated: **12 April 2017**



Date last updated: **12 April 2017**

Disclaimer: The Product Technical Statement (PTS) template is copyright to Construction Information Limited. However the content of this PTS is the responsibility of the product manufacturer/supplier. Refer to the miproducts Terms and Conditions