



Product overview

Vertiface® is a durable, versatile wallcovering made from 100% polyester fibre. With a soft velour finish on one side, and sleek flat pile on the other, Vertiface can be used as a furnishing fabric, wallcovering, and acoustic panel overlay. Vertiface is hook-and-loop receptive and pinnable with a self-healing surface.

Sustainable material

- Carbon neutral product
- Zero carbon manufacturing
- Recycled content
- >80% recycled material
- Low VOC and CDPH compliant
- <0.0035 mg/m³ (7 days)
- Zero waste manufacturing initiative
- Sustainable supply chain and anti-modern slavery

Environmental certifications

- EPD – compliant with ISO 14025 and EN 15804
- Declare – Red List free (third party verified)
- ISO 14001 Certified Environmental Management
- Health Product Declaration
- CDPH Standard



Certifying your green building

Autex Acoustics products meet criteria for WELL, LEED, Green Star, and BREEAM building rating systems, helping you achieve certification for your project. For support and guidance on available rating system points please visit www.autexglobal.com, or speak with your Autex Acoustics account manager.

Specification

(Wall) treatment shall be Vertiface® made from non-woven needle-punched polyester containing no less than 80% recycled material as manufactured by Autex www.autexglobal.com

Roll 3 - 4 mm (nom.) depth, colour (), Fire Rating ISO 9705: Classification: Group 1-S, AS ISO 9705 – 2003 Classification: Group 1, EN13501-1:2007+A1:2009: B - s1, d2

Product specifications

Product name Vertiface®
Composition 100% polyester fibre (PET)
Roll dimensions 1.3 m x 50 m
Tolerance (+ 5 mm) x (+ 10 mm)
Thickness (nom.) 3 - 4 mm
Weight Typically 380 gsm

Installation

Install as per Autex Acoustics recommendations. Install instructions are included in each pack or available on the website.

If Vertiface is to be specified for use other than as a wallcovering, please seek guidance from your account manager.

Other widths are available on request, MOQ's apply.



Product specifications

Fire ratings

Vertiface has been evaluated using the following test methods

ISO 9705: 1993

Classification: Group 1-S

Smoke production rate:

<5.0m²/s

As required by NZBC C/VM2

AS ISO 9705 - 2003

Classification: Group 1

(SMOGR_{ARC}): <100m²/s²

Assessed using methodology AS ISO 9705:2003 in accordance with AS 56371:2015, as required by BCA Specification C1.10-4 FI 4906 FAR 4055

BS EN 13501-1:2018

Classification: B-s1,d0

Tested using BS EN ISO 11925-2:2020 and BS EN 13823:2020 and classified in accordance with BS EN 13501-1:2018, as required by BS EN 15102:2007 + A1:2011. EUI-21-000135-C

ASTM E84 - 01

Class A, FS:20 - SD:50

01.04913.01.206a

Water vapour sorption

ASTM C1104 / C1104M-13a

Test conditions: 49°C, 95%RH

Water vapour absorbed and adsorped after

4 days: 0.4% by weight

Microbial resistance

ASTM G21-15

Growth rating: 0 (No growth)

Vertiface does not promote the growth of moulds and mildew.

Colour fastness to light

Vertiface is suitable for indoor

use only. Light fastness

is dependent on use and

exposure. Vertiface has

been evaluated to the

following standard:

ISO 105-B02:2014

Rating: 6 (Highest = 7)

Colour fastness to rubbing

ISO 105-X12:2016

Dry rating: 4-5 (Highest = 5)

Wet rating: 4-5 (Highest = 5)

Pattern repeat

Non-woven. No pattern repeat

but product has directional

grain. Product may vary from

samples and batch to batch

due to fibre blending and

lay-up, which is an inherent

feature of this product.

Fabric care

Blot spills from fabric quickly.

Wipe with a damp cloth. Avoid

rubbing and excessive amounts

of water as this will affect the

finish. Use carpet or upholstery

shampoo as directed. Blot with

a clean dry cloth after each

application of solution.

Custom printed Vertiface requires the services of a specialist cleaning company. Refer to the Vertiface Care and Maintenance Guide for more information.

Service

For further information about Vertiface or any other Autex Acoustics product, please contact your account manager or visit our website.

Light reflectance values by colour

Vertiface LRVs were measured in accordance with BS 8493:2008+A1:2010

Acros	30	Lime	29
Atlantis	8	Muralla	7
Beehive	30	Myst	42
Blazing Red	8	Octane	5
Calypso	13	Opera	47
Canyon	14	Parthenon	28
Caspian	3	Petronas	1
Cavalier	10	Pinnacle	2
Chilli Red	5	Porcelain	22
Electric Blue	12	Sage	9
Empire	3	Sargazo	2
Falling Water	32	Savoye	44
Flatiron	23	Senado	45
Gherkin	5	Simba	18
Granny Smith	20	Spearmint	13
Highland	14	Stonewash	19
Ink	3	Terrace	18
Jade	22	Tree House	2
Koala	12	Vintage	6

● **New Zealand**
702-718 Rosebank Road,
Private Bag 19988
Avondale 1746, Auckland
T 0800 428 839
T +64 9 828 9179
www.autexacoustics.co.nz

● **Australia**
285 Swan Street,
Richmond, VIC 3121
T 1800 678 160
T +61 3 9450 6700
www.autexacoustics.com.au

● **United Kingdom**
Unit J4, Lowfields Way,
Lowfields Business Park,
Elland, West Yorkshire
HX5 9DA
T +44 0 142 241 8899
www.autexacoustics.co.uk

● **United States**
1630 Dan Kipper Drive,
Riverside, CA 92507
T +1 424 203 1813
www.autexacoustics.com

Autex is an ISO certified organisation encompassing Quality (ISO 9001), Environmental (ISO 14001), and Health and Safety (ISO 45001). Brand names and logos are registered or unregistered trademarks owned or used under license by Autex Industries Limited or other members of the Autex Group. © Copyright 2023 Autex Industries Ltd. All rights reserved. It is the user's responsibility to determine if the product and information presented in this document is suitable for the intended application by engaging a suitably qualified consultant. The information contained in this document is correct to the best of our knowledge at the date of its publication. To verify that this document is the most current publication please check our website or contact your Autex account manager.