Composition® is a durable and flexible acoustic wallcovering. <u>View miproducts listing</u>



Level of assurance needed to demonstrate NZ Building Code Compliance

Supporting documentation should include self-assessment and technical information by manufacturer



Autex confirms that this minimum level of assurance has been met or exceeded by the following: Autex Industries Limited <u>New Zealand Made Certificate - 705337</u>

Technical Statement

Product Description

Autex Composition is an acoustic wallcovering designed to reduce reverberated noise by up to 40% (NRC 0.4) Available in 34 fashionable colours in either roll form or self adhesive Peel and Stick tiles

New Zealand Building Code (NZBC)

The product will, if employed in accordance with the supplier's installation and maintenance requirements, assist with meeting the following provisions of the building code:

- Clause B2 Durability: Performance B2.3.1(c)
- Clause C3 Fire affecting areas beyond the fire source: Performance C3.4(a)

<u>Notes</u>

FIRE RATINGS

ISO 9705: 1993

Classification: Group 1-S Smoke Production Rate: <5.0m2/s As required by NZBC C/VM2

AS ISO 9705 - 2003

Classification: Group 1 (SMOGRArc): <100m2/s2 Assessed using methodology AS ISO 9705:2003 in accordance with AS 5637.1:2015, as required by BCA Specification C1.10-4 *FI* 4894 and FAR 4055

EN13501-1:2007 B - s1, d0 *Report 189053*

Supporting Evidence

The product has and can make available the following additional evidence to support the above statements:

Autex Industries Limited <u>New Zealand Made Certificate - 705337</u>

Product Criteria

Design requirements

Performance

Composition® has been tested to a Noise Reduction Coefficient (NRC) of 0.4 and will typically reduce reverberated noise by approximately 40%

Fire Ratings

ISO 9705: 1993 Classification: Group 1-S Smoke Production Rate: <5.0m2/s As required by NZBC C/VM2

AS ISO 9705 - 2003 Classification: Group 1 (SMOGRArc): <100m2/s2 Assessed using methodology AS ISO 9705:2003 in accordance with AS 5637.1:2015, as required by BCA Specification C1.10-4 FI 4894 dated 6th June, 2012 and FAR 4055-2 dated 8th October, 2013

EN13501-1:2007 B - s1, d0 Report 189053 dated 7th December, 2009





masterspec partner

Company Contact Details	
	TM
Brand:	Autex Acoustics®
Company:	Autex Acoustics
Physical Address:	702/718 Rosebank Road Avondale Auckland
Postal Address:	Private Bag 19988 Avondale AUCKLAND
Telephone:	64 800 428839
Email:	enquiries@autex.co.nz
Website:	https://www.autexacoustics.co.nz/products/composition

Autex Composition® Product Technical Statement: 101388

Installation requirements

Please refer to our website for Installation Instructions: http://www.autexindustries.com/acoustics/composition/

Company Product Information

Environmental

ENVIRONMENTAL

Autex is committed to best practice through our ISO 9001 and ISO 14001 certified Quality and Environmental Management Systems.

Composition products contains a minimum of 45% recycled polyester fibre (from PET bottle-flake). Off-cuts and manufacturing waste is re-used or recycled wherever possible.

Uncontaminated Composition can be recycled. For further information, please call Autex on 0800 428 839.

Composition is manufactured from 100% polyester fibres and does not contain formaldehyde binders. Autex polyester fibres support safer indoor air quality and will not become a potential airborne pollutant.

Quality Assurance



ISO 9001 (Quality Management)

Relationships



 \checkmark

New Zealand Made

Date last validated: 17 October 2022

Date last updated: 17 October 2022

Disclaimer: The Product Technical Statement (PTS) template is copyright to Construction Information Limited. However the content of this PTS is the responsibility of the product manufacturer/supplier. Refer to the miproducts Terms and Conditions

±