

Premium polystyrene (EPS) sheet. High R-values.

[View miproducts listing](#)



## Level of assurance needed to demonstrate NZ Building Code Compliance

*Supporting documentation should include self-assessment and technical information by manufacturer*



EXPOL confirms that this minimum level of assurance has been met or exceeded by the following:

AWTA

[Neopor](#)



**masterspec partner**

## Technical Statement

### Scope of use

Applications include:

- MASONRY WALL INSULATION
- UNDER CONCRETE FLOOR INSULATION
- SKILLION ROOF INSULATION
- EPS CLADDING SYSTEMS

### New Zealand Building Code (NZBC)

The product will, if employed in accordance with the supplier's installation and maintenance requirements, assist with meeting the following provisions of the building code:

- **Clause B2 Durability:** Performance B2.3.1(a)
- **Clause E3 Internal moisture:** Performance E3.3.1
- **Clause F2 Hazardous building materials:** Performance F2.3.1
- **Clause H1 Energy efficiency :** Performance H1.3.1, H1.3.2E

### Evidence

The product meets the requirements set out in the following documents, or relevant parts of cited standards within the documents:

MANUFACTURING STANDARD - Expol Platinum Board complies with manufacturing standard AS 1366 Part 3 1992.

### Supporting Evidence

The product has and can make available the following additional evidence to support the above statements:

AWTA

[Neopor](#)

## Product Criteria

### Design requirements

EXPOL Platinum Board is a premium insulation panel designed for use in situations where a high R value is required within a shallow cavity or where rigid panels is required.

This product can not be used where exposed to direct sunlight.

### SYSTEM COMPONENTS

#### WIRE GUARD

EXPOL Wireguard is a waxed paper strip used to separate exposed electrical cables from EXPOL insulation. EPS in some cases reacts with the plasticiser and degrades the elastic properties of some electrical cables over a prolonged period.

#### STYROFIX CONSTRUCTION ADHESIVE

EXPOL supplies a low solvent glue designed to adhere polystyrene to most surfaces. EXPOL Platinum Board can be glued in place using this adhesive.

### Installation requirements

Install the polystyrene sheets once the polythene DPM has been laid. Place the polystyrene sheets on top of the polythene DPM and butt together. Do not place the polystyrene under any footings or thickenings. Cut holes in the polystyrene with a sharp knife to accommodate any services. Lay reinforcing steel mesh over the polystyrene on mesh chairs.

### Company Contact Details



Company:	Expol Limited
Physical Address:	105 Captain Springs Road Onehunga AUCKLAND
Postal Address:	PO Box 13560 Onehunga AUCKLAND
Telephone:	64 09 6343449
Fax:	64 09 6340756
Email:	<a href="mailto:sales@expol.co.nz">sales@expol.co.nz</a>
Website:	<a href="http://www.expol.co.nz">www.expol.co.nz</a>

## Company Product Information

### Videos

[EXPOL Platinum Board](#)



Date last validated: **27 September 2023**



Date last updated: **27 September 2023**

Disclaimer: The Product Technical Statement (PTS) template is copyright to Construction Information Limited. However the content of this PTS is the responsibility of the product manufacturer/supplier. Refer to the miproducts Terms and Conditions