

# Earthwool® Glasswool insulation ceiling segments

Product Technical Statement: 108930



Earthwool® Glasswool is made using ECOSE® Technology, a plant-based binder with no added formaldehyde

[View miproducts listing](#)



## Level of assurance needed to demonstrate NZ Building Code Compliance

Supporting documentation should include self-assessment and technical information by manufacturer



Earthwool® Glasswool insulation confirms that this minimum level of assurance has been met or exceeded by the following:

CodeMark

[30095](#)

BRANZ Appraisal

[648](#)



The following information has been provided by Earthwool® Glasswool insulation demonstrating how this product complies with the [Building Product Information Requirements](#).

## Technical Statement

### Product Class

CLASS 1

### Product Description

Earthwool® Glasswool ceiling insulation is a high-performance solution designed to support compliance with building code and project design requirements in New Zealand. Manufactured with a patented plant-based binder, it contains no added formaldehyde, petro-based chemicals or artificial colours. Its natural brown appearance reflects this more sustainable formulation, while the soft-touch finish also supports easier handling and installation on site.

### Scope of use

Supply and install the selected Earthwool® Glasswool insulation to ceilings, roofs and other areas as identified on the drawings, complete with accessories.

All aspects of this work shall be in complete accordance with Knauf Insulation product manuals and installation guides, (check [www.knauf.com/en-NZ](http://www.knauf.com/en-NZ), or call 0800 562 834 for the latest editions), Earthwool® Glasswool insulation BRANZ Appraisal, other relevant product manufacturers' recommendations, and as shown on the drawings.

No substitutions are permitted for Earthwool® Glasswool insulation.

### New Zealand Building Code (NZBC)

The product will, if employed in accordance with the supplier's installation and maintenance requirements, assist with meeting the following provisions of the building code:

- Clause B2 Durability:** Performance B2.3.1(a), B2.3.1(b)  
<https://knauf.com/api/download-center/v1/assets/0c2cb7ad-9c69-470d-be3f-83206b89ea51?download=true&country=nz>
- Clause E3 Internal moisture:** Performance E3.3.1  
<https://knauf.com/api/download-center/v1/assets/0c2cb7ad-9c69-470d-be3f-83206b89ea51?download=true&country=nz>
- Clause F2 Hazardous building materials:** Performance F2.3.1  
<https://knauf.com/api/download-center/v1/assets/0c2cb7ad-9c69-470d-be3f-83206b89ea51?download=true&country=nz>
- Clause G6 Airborne and impact sound:** Performance G6.3.1  
<https://knauf.com/api/download-center/v1/assets/0c2cb7ad-9c69-470d-be3f-83206b89ea51?download=true&country=nz>
- Clause H1 Energy efficiency :** Performance H1.3.1, H1.3.1(a), H1.3.2E  
<https://knauf.com/api/download-center/v1/assets/0c2cb7ad-9c69-470d-be3f-83206b89ea51?download=true&country=nz>

### Evidence

The product meets the requirements set out in the following documents, or relevant parts of cited standards within the documents:



masterspec partner

### Company Contact Details

**EARTHWOOL®**  
the feel good glasswool insulation  
**GLASSWOOL**

Brand: Earthwool® Glasswool insulation

Company: Knauf Insulation New Zealand

Physical Address: PO Box 512 Auckland

Postal Address: PO Box 512 Silverdale Auckland

Email: [tech.nz@knaufinsulation.com](mailto:tech.nz@knaufinsulation.com)

Website: <http://www.knauf.com/en-NZ/knauf-insulation>

# Earthwool® Glasswool insulation ceiling segments

Product Technical Statement: 108930



Earthwool Glasswool insulation is an Acceptable Solution in terms of New Zealand Building Code Compliance.

Earthwool Glasswool insulation thermal resistance (R-value) is declared in accordance with the requirements of AS/NZS 4859.1 which is an acceptable method.

## Supporting Evidence

The product has and can make available the following additional evidence to support the above statements:



CodeMark

30095

BRANZ Appraisal

648

## Product Criteria

### Design requirements

Earthwool® Glasswool Ceiling segments are designed to deliver reliable thermal and acoustic performance for energy-efficient residential and commercial buildings. Suitable for use in both timber and metal-framed ceiling applications, they provide a cost-effective insulation solution for projects requiring compliance with thermal and acoustic design objectives. Manufactured for consistent quality and ease of installation, the batts are low dust, clean cutting and highly resilient, allowing them to recover quickly to full thickness. Earthwool® Glasswool Ceiling segments also incorporate DriTherm® Technology, which provides moisture repellence to support long-term durability and in-service performance.

### Installation requirements

Installation of Earthwool Glasswool insulation must be completed by an installer with an understanding of insulation installation, in accordance with the instructions given within the Technical Literature, Installation Instructions and BRANZ Appraisal.

Installation of Earthwool Glasswool insulation must be in accordance with the Knauf Insulation's Technical Literature, Installation Instructions and BRANZ Appraisal.

NZS 4246 should be used as a guide for installing insulation in residential buildings in New Zealand.

The product must be installed only when the building is enclosed and when the construction materials have achieved the required maximum moisture content or less, to ensure the insulation does not become wet.

### Maintenance requirements

The building must be maintained weatherproof at all times.

If, during normal routine maintenance it is discovered that moisture has entered the building envelope, or that dampness has occurred because of leaking plumbing or some other source, then that source must be repaired immediately.

Wet or damp insulation must be removed and then replaced with new insulation of an equivalent thermal rating.

Cavities must be clean, dry and free of all contaminants and mould before fitting new insulation.

NZS 4246 Paragraph 3.3 gives guidance on thermal insulation maintenance due to water damage.

### Warrantees

Knauf Insulation Pty Ltd (ACN 129 827 336) and Knauf Insulation Ltd (Registered NZ Company No. 35 271 92) - (Knauf) - warrant that Earthwool® Glasswool insulation products (Product) are manufactured in accordance with AS/NZS-4859.1 and are fit for the purpose of insulating ceilings, external timber frame walls, underfloors and internal acoustic partitions, if tested in accordance with the methodology referred to in AS/NZS-4859.1, if properly installed in accordance with the installation instructions and if maintained according to relevant Standards including AS-3999/NZS-4246.

Conditions apply - visit the following link for full warranty details and conditions: <https://knauf.com/en-NZ>

## Company Product Information

### Environmental

Earthwool® Glasswool products are manufactured using recycled glass and have GreenRate™ Level A certification. Certification makes it easy for designers and building owners to gain rewards under Green Star and Homestar credits system. Earthwool® Glasswool has been certified Declare Red List Free label meaning that none of the raw materials used in its manufacture are on the International Living Futures Institute red list. Earthwool® Glasswool is also free from CFCs, HCFCs and any other material with known ozone depletion potential and represents no known threat to the environment. Knauf Insulation's unique binder technology - ECOSE® Technology - is plant-based and is based on rapidly renewable materials, instead of petro-based chemicals. ECOSE® Technology results in less embodied carbon than traditional binders used in alternative glasswool products.

# Earthwool® Glasswool insulation ceiling segments

Product Technical Statement: 108930



## Quality Assurance



ISO 9001 (Quality Management)

## Relationships



Member of New Zealand Green Building Council



Eurofins Gold level - No. lacg-323-01-25-2022



International Living Futures Institute International Living Futures Institute



CodeMark 30095



Jensen Hughes AC100.3



EcoSpecifier Global GreenTag Level A

## Videos

[Double vs Single Layer Ceiling Insulation](#)

[Earthwool Glasswool Skillion Roof Case Study](#)

## Building Product Information Requirements

### Manufacturer

#### Legal Trading Name:

Knauf Insulation New Zealand

#### Business Email:

tech.nz@knaufinsulation.com

#### Company Website:

<http://www.knauf.com/en-NZ/knauf-insulation>

#### Contact Number/s:

0800 562834

### Product Identifier

R-VALUE THICKNESS (MM) WIDTH (MM) LENGTH (MM) M2/PACK 3.4 110 580 1160 4.71 3.6  
175 430 1160 8.48 4.1 195 430 1160 7.48 5.2 210 430 1160 5.49 7 330 460 1160 4.42 8 330  
460 1160 3.31

### Warnings

This product has no warnings associated with it.



Date last validated: **06 July 2026**



Date last updated: **06 July 2026**

Disclaimer: The Product Technical Statement (PTS) template is copyright to Construction Information Limited. However the content of this PTS is the responsibility of the product manufacturer/supplier. Refer to the miproducts Terms and Conditions