# Earthwool® glasswool insulation Roof blanket

miproducts

Earthwool® glasswool is made using recycled glass and with ECOSE® Technology. View miproducts listing



## Level of assurance needed to demonstrate NZ Building Code Compliance

Supporting documentation should include self-assessment and technical information by manufacturer





Earthwool® glasswool insulation confirms that this minimum level of assurance has been met or exceeded by the following: **BRANZ Appraisal** 



## **Technical Statement**

#### Scope of use

Supply and install the selected Earthwool® glasswool insulation to walls, floors, ceilings, roofs and other areas as identified on the drawings, complete with accessories.

All aspects of this work shall be in complete accordance with Knauf Insulation product manuals and installation guides, (check www.knaufinsulation.co.nz, or call 0800 562 834 for the latest editions), Earthwool® glasswool insulation BRANZ Appraisal, other relevant product manufacturers' recommendations, and as shown on the drawings.

No substitutions are permitted for Earthwool® glasswool insulation.

### New Zealand Building Code (NZBC)

The product will, if employed in accordance with the supplier's installation and maintenance requirements, assist with meeting the following provisions of the building code:

- Clause B2 Durability: Performance B2.3.1(a), B2.3.1(b)
- Clause E3 Internal moisture: Performance E3.3.1
- Clause F2 Hazardous building materials: Performance F2.3.1
- Clause H1 Energy efficiency: Performance H1.3.1, H1.3.2E

## **Evidence**

The product meets the requirements set out in the following documents, or relevant parts of cited standards within the documents:

Earthwool glasswool insulation is an Acceptable Solution in terms of New Zealand Building Code

Earthwool glasswool insulation thermal resistance (R-value) has been determined by testing to AS/NZS 4859.1 which is an acceptable method.

## Supporting Evidence

The product has and can make available the following additional evidence to support the above statements:



**BRANZ Appraisal** 648

## **Product Criteria**

#### **Design requirements**

Earthwool glasswool insulation: Roof blankets provide a cost-effective thermal and acoustic barrier for energy-efficient construction. The consistent quality, low dust, and clean-cutting resilient fibres make fabrication easy and installation fast.

Earthwool glasswool insulation: Roof blankets can be used in timber and metal frame applications in residential structures. These applications include thermal and acoustic treatments to walls, ceilings and mid floors.

Knauf Insulation offers Earthwool glasswool insulation in a wide range of sizes and R-values. Earthwool glasswool insulation can be used for cavity walls, floors, ceilings, attics, basements and crawlspaces. It is highly resilient, recovering quickly to full thickness. It also greatly reduces the transmission of noise in the home.

## Installation requirements

Installation of Earthwool glasswool insulation must be completed by an installer with an understanding of insulation installation, in accordance with the instructions given within the Technical

# masterspec partner

## Company Contact Details **ARTHWOOL**

## the feel good glassmal insulation **GLASSWOOL**

Earthwool® glasswool Brand insulation

Company: Knauf Insulation New Zealand PO Box 217 063

Auckland PO Box 217 063 Postal Address: **Botany Junction** 

Physical

Auckland

tech.nz@knaufinsulation.com

http://www.knaufinsulation.co.nz

# Earthwool® glasswool insulation Roof blanket

Product Technical Statement: 104859



Literature, Installation Instructions and BRANZ Appraisal.

Installation of Earthwool glasswool insulation must be in accordance with the Knauf Insulation's Technical Literature, Installation Instructions and BRANZ Appraisal.

NZS 4246 should be used as a guide for installing insulation in residential buildings in New Zealand.

The product must be installed only when the building is enclosed and when the construction materials have achieved the required maximum moisture content or less, to ensure the insulation does not become wet.

## Maintenance requirements

The building must be maintained weatherproof at all times.

If, during normal routine maintenance it is discovered that moisture has entered the building envelope, or that dampness has occurred because of leaking plumbing or some other source, then that source must be repaired immediately.

Wet or damp insulation must be removed and then replaced with new insulation of an equivalent thermal rating.

Cavities must be clean, dry and free of all contaminants and mould before fitting new insulation.

NZS 4246 Paragraph 3.3 gives guidance on thermal insulation maintenance due to water damage.

## **Company Product Information**

## **Environmental**

Earthwool glasswool insulation: Roof blankets are free from CFCs, HCFCs and any other material with ozone depletion potential in its manufacture and content and represents no known threat to the environment

Earthwool glasswool insulation: Roof blankets' manufacture has a low impact on the environment and is classified as Zero ODP and Zero GWP.

Knauf Insulation mineral wool products with ECOSE Technology benefit from a revolutionary, biobased, formaldehyde-free binder technology, based on rapidly renewable materials, instead of petrobased chemicals. It reduces embodied energy and delivers superior environmental sustainability.

The technology has been developed for Knauf Insulation's glass and rock mineral wool products, enhancing their environmental credentials without affecting the thermal, acoustic or fire performance. Insulation products made with ECOSE Technology contain no dye or artificial colours - the colour is completely natural.

#### **Quality Assurance**



ISO 9001 (Quality Management)

## Relationships



Member of New Zealand Green Building Council



EcoSpecifier Global GreenTag Level A



Date last validated: 07 July 2020



Date last updated: 07 July 2020

Disclaimer: The Product Technical Statement (PTS) template is copyright to Construction Information Limited. However the content of this PTS is the responsibility of the product manufacturer/supplier. Refer to the miproducts Terms and Conditions