

Durable wall finish, ideal for both work and living spaces

[View miproducts listing](#)



Level of assurance needed to demonstrate NZ Building Code Compliance

Supporting documentation should include technical information by manufacturer and either an independent assessment or reference to an industry-based scheme



James Hardie confirms that this minimum level of assurance has been met or exceeded by the following:

James Hardie

[Invibe Panel](#)

Technical Statement

Product Description

ARChitectural™ Invibe™ panel is an internal pre-finished panel.

Invibe™ panel's core DNA is durability, because it's made from James Hardie® 6mm thick cement-composite substrate that's coated using ChromaShield™ 200 series. Invibe™ panel offers a 'double shield' of durability in a vast range of commercial and residential interior wall applications in both wet and dry areas.

Sheet size: 2700 x 1200mm Thickness: 6mm Finish: Gloss or Satin

Application: Commercial and residential interior wall in both wet and dry areas.

Scope of use

Commercial and residential interior wall applications in both wet and dry areas.

New Zealand Building Code (NZBC)

The product will, if employed in accordance with the supplier's installation and maintenance requirements, assist with meeting the following provisions of the building code:

- **Clause B1 Structure:** Performance B1.3.1, B1.3.2, B1.3.3(j)
- **Clause B2 Durability:** Performance B2.3.1(b)
- **Clause C3 Fire affecting areas beyond the fire source:** Performance C3.4(a)
- **Clause E3 Internal moisture:** Performance E3.3.4, E3.3.5, E3.3.6
- **Clause F2 Hazardous building materials:** Performance F2.3.1
- **Clause H1 Energy efficiency :** Performance H1.3.1

Notes

Invibe panel complies with the requirements of section 3.1.2 of Clause E3/AS1 of the NZBC. Invibe panel must be installed in accordance with this specification to satisfy the relevant provisions of the NZBC.

Supporting Evidence

The product has and can make available the following additional evidence to support the above statements:

James Hardie

[Invibe Panel](#)

Product Criteria

Design requirements

Invibe panel is suitable for use in wet or dry areas that require an impervious and a low maintenance surface.

Installation requirements

Refer to the Invibe panel Installation Manual.

[INvibe panel installation manual](#)

Warrantees

INvibe panel has a standard product warranty of 10 years for coating and 15 years for base sheet when installed and maintained as per the Installation Manual.

Company Product Information



masterspec partner

Company Contact Details



JamesHardie™

Company: James Hardie

Physical Address: 1 O'Rorke Road
Penrose
AUCKLAND

Postal Address: PO Box 12070
Penrose
AUCKLAND

Fax: 64 09 5254810

Email: info@jameshardie.co.nz

Website: www.jameshardie.co.nz

Environmental

We aim to conduct business in an environmentally sound and sustainable manner and to use management systems and operating procedures to identify, monitor, control and reduce the impact of our operations and our products on the environment. We strive to continually improve our manufacturing processes and product formulations to minimise our carbon footprint. As such, we are committed to ecologically sustainable development (ESD) principles. James Hardie is a founding participant in the Commonwealth Governments Greenhouse Challenge to voluntarily reduce greenhouse gas emissions and undertake emission abatement plans.

Quality Assurance



ISO 9001 (Quality Management)

Relationships



New Zealand Made



Date last validated: **13 May 2022**



Date last updated: **13 May 2022**

Disclaimer: The Product Technical Statement (PTS) template is copyright to Construction Information Limited. However the content of this PTS is the responsibility of the product manufacturer/supplier. Refer to the miproducts Terms and Conditions