

Externally spray-applied, instant cure, seamless, rubber waterproofing membrane

[View miproducts listing](#)



Level of assurance needed to demonstrate NZ Building Code Compliance

Supporting documentation should include technical information by manufacturer and either an independent assessment or reference to an industry-based scheme




Newton confirms that this minimum level of assurance has been met or exceeded by the following:

CodeMark

[BCS164618-CMNZ](#)

Kiwa

[Kiwa BDA Agrément - BAB 17-031/04/A](#)



masterspec partner

Company Contact Details



Company: Newton Systems Limited

Physical Address: Broadway
Newmarket
Auckland

Postal Address: P0 Box 9446,
Newmarket
Auckland

Telephone: 64 21 2410452

Email: stuart@newtonsystems.co.nz

Website: www.newtonsystems.co.nz

Technical Statement

Scope of use

Newton 108 HydroBond-LM is suitable for all below-ground and earth-retained structures, ranging from domestic basements to the largest civil engineering projects

New Zealand Building Code (NZBC)

The product will, if employed in accordance with the supplier's installation and maintenance requirements, assist with meeting the following provisions of the building code:

- **Clause B1 Structure:** Performance B1.3.3(e), B1.3.3(j), B1.3.3(m), B1.3.3(q)
- **Clause B2 Durability:** Performance B2.3.1(a)
- **Clause E2 External moisture:** Performance E2.3.3
- **Clause F2 Hazardous building materials:** Performance F2.3.1

Supporting Evidence

The product has and can make available the following additional evidence to support the above statements:



CodeMark

[BCS164618-CMNZ](#)



Kiwa

[Kiwa BDA Agrément - BAB 17-031/04/A](#)

Product Criteria

Design requirements

Newton 108 HydroBond-LM is normally specified as part of our Newton HydroBond System in conjunction with Newton 403 HydroBond, the membrane can also be used on its own, terminating to raft or strip foundations. Newton 108 HydroBond-LM is very quick to apply, it can be applied in cooler and damper conditions, and without a primer.

Installation requirements

Newton 108 HydroBond-LM can only be sprayed with a specialist spray machine. The Newton 108 HydroBond-LM is required to be designed and installed according to the details and drawings described in technical and installation manual, by Newton System's trained and approved applicators. When used in conjunction with Newton 403 HydroBond or 403 HydroBond-GB as a full HydroBond System, overlap by a minimum of 150 mm. Installation temperature +5 to +35 °C.

Maintenance requirements

Newton 108 HydroBond-LM is extremely puncture resistant, with high elasticity and a 95% recovery memory. The membrane is not hard wearing and should be protected during back-filling.

Warrantees

Correctly installed and fully and permanently isolated from UV light and physical damage or wearing, the **Newton HydroBond 108-LM** will provide, under normal service conditions, a durable waterproof barrier for the life of the building to which it is installed. The expected life time of the building itself should be at least 50 years. Please note that this is not the guarantee. The waterproofing guarantee is provided by the specialist waterproofing applicator who installs the product.

Company Product Information

Newton 108 HydroBond-LM

Product Technical Statement: 109707



Environmental

Newton HydroBond 108-LM - material composition: Polymer modified bituminous thick coatings for waterproofing.

Quality Assurance



ISO 9001 (Quality Management)

Videos

[108 HydroBond-LM](#)



Date last validated: **30 September 2019**



Date last updated: **30 September 2019**

Disclaimer: The Product Technical Statement (PTS) template is copyright to Construction Information Limited. However the content of this PTS is the responsibility of the product manufacturer/supplier. Refer to the miproducts Terms and Conditions