

# Resene Construction Systems Insulated Facade System - Graphex

Product Technical Statement: 103477



This system consists of a 40mm or 60mm Neopor board with a 5 - 6mm plaster coating & paint

[View miproducts listing](#)



## Level of assurance needed to demonstrate NZ Building Code Compliance

Supporting documentation should include technical information by manufacturer and either a BRANZ or independent Appraisal or CodeMark



Resene Construction Systems confirms that this minimum level of assurance has been met or exceeded by the following:

BRANZ Appraisal

[633](#)

## Technical Statement

### Scope of use

Installed on Timber frame or steel frame construction

Graphex Cavity System has been appraised as an external wall cladding system for buildings within the following scope;

- The scope limitations of NZBC Acceptable Solution E2/AS1, paragraph 1.1; and,
- Constructed with timber frame complying with the NZBC; and,
- With a risk score of 0-20, calculated in accordance with NZBC Acceptable Solution E2/AS1, Table 2; and,
- Situated in NZS 3604 Wind Zone up to and including 'Extra High'

### New Zealand Building Code (NZBC)

The product will, if employed in accordance with the supplier's installation and maintenance requirements, assist with meeting the following provisions of the building code:

- **Clause B1 Structure:** Performance B1.3.1, B1.3.2, B1.3.4
- **Clause B2 Durability:** Performance B2.3.1(b), B2.3.1(c)
- **Clause E2 External moisture:** Performance E2.3.2
- **Clause F2 Hazardous building materials:** Performance F2.3.1

### Notes

Durability applies 15 Years for the cladding system and plaster finish, and 5 years for the exterior paint system

### Evidence

The product meets the requirements set out in the following documents, or relevant parts of cited standards within the documents:

The Graphex Insulated Facade System is a cavity-based Exterior Insulation and Finishing (EIFS) wall cladding. It is designed to be used as an external cladding system for residential and light commercial type buildings where domestic construction techniques are used.

### Supporting Evidence

The product has and can make available the following additional evidence to support the above statements:



BRANZ Appraisal

[633](#)

## Product Criteria

### Design requirements

### Installation requirements

Installed by a LBP tradesman and a Resene Construction Systems Registered Plasterer

### Maintenance requirements

Carry out an annual inspection and record this on the Resene Construction Systems Maintenance guide. For best results use Resene Paint Prep and Housewash liquid concentrate. Apply the diluted solution with a soft broom, and wash off with copious amounts of fresh water. Most detergents have a detrimental effect on fish life so avoid letting the washings run off into the storm-water system. DO NOT use harsh solvent based cleaners.

**masterspec partner**

#### Company Contact Details

**Resene**  
Construction Systems

Company: Resene Construction Systems

Physical Address: 5 Venture Place

Middleton

Christchurch

Postal Address: PO Box 39108

Harewood  
CHRISTCHURCH

Telephone: 64 6328 3386328

Fax: 64 03 3386819

Email: [mark@reseneconstruction.co.nz](mailto:mark@reseneconstruction.co.nz)

Website: [www.reseneconstruction.co.nz](http://www.reseneconstruction.co.nz)

# Resene Construction Systems Insulated Facade System - Graphex

Product Technical Statement: 103477



## Company Product Information

### Relationships



New Zealand Made



Member of New Zealand Green Building Council



Date last validated: **12 January 2021**



Date last updated: **12 January 2021**

Disclaimer: The Product Technical Statement (PTS) template is copyright to Construction Information Limited. However the content of this PTS is the responsibility of the product manufacturer/supplier. Refer to the miproducts Terms and Conditions