

Feature some grey schist from Central Otago. Available in walling, with formed corners

[View miproducts listing](#)



## Level of assurance needed to demonstrate NZ Building Code Compliance

Supporting documentation should include technical information by manufacturer and either an independent assessment or reference to an industry-based scheme



SUMNER confirms that this minimum level of assurance has been met or exceeded by the following:

CodeMark

[BCS-141814-CMNZ](#)

## Technical Statement

### Scope of use

SUMNER is direct fix unless used as a cladding, in which case we supply our own proprietary cavity system (rigid backer and cavity battens).

- a) Up to 3 storeys, or 10m to top of chimney
- b) With floor plan area limited only by seismic and structural control joints, and
- c) External walls that are vertical, and roofs that are 60° or less above the horizontal, and
- d) Buildings that require specific design input must have framing stiffness equal to the framing provisions of NZS 3604, and Timber frame constructions complying with the NZBC, and Steel frame constructions must be to a specific design meeting the requirements of the NASH 3405, and Masonry constructions complying with NZS3604:2011, and Suitable for residential and commercial applications, in locations where the maximum wind zone is determined to be less than or equal to very high (50m/s).

### New Zealand Building Code (NZBC)

The product will, if employed in accordance with the supplier's installation and maintenance requirements, assist with meeting the following provisions of the building code:

- **Clause B1 Structure:** Performance B1.3.2, B1.3.3, B1.3.3(a), B1.3.3(f)
- **Clause B2 Durability:** Performance B2.3.1(a), B2.3.1(b), B2.3.1(c)
- **Clause E2 External moisture:** Performance E2.3.2
- **Clause F2 Hazardous building materials:** Performance F2.3.1

### Evidence

The product meets the requirements set out in the following documents, or relevant parts of cited standards within the documents:

SUMNER Board complies with AS/NZS 2908.2:2000, and NZBC clause B1

### Supporting Evidence

The product has and can make available the following additional evidence to support the above statements:



CodeMark

[BCS-141814-CMNZ](#)

## Product Criteria

### Design requirements

Used for cladding of steel, timber frame and masonry buildings, with wind speed up to 50 m/s (Very High). Use our Codemark for ease of compliance.

Unlimited use any landscaping application

### Installation requirements

The SUMNER System must only be installed on vertical surfaces in accordance with the Technical Literature. Wind Zone Suitable for locations where the maximum wind zone is determined to be less than or equal to very high (50m/s), or where specific design is employed. Where SUMNER Schist cladding system is to be used for High-wind zones a Rigid Air Barrier compliant with NZBC must be employed. SUMNER has also been appraised for weather tightness and structural wind loading when used for timber or steel framed buildings subject to specific design up to a design



### Company Contact Details



Brand: SUMNER

Company: SUMNER Schist cladding

Physical Address: 177 Marua Rd  
Ellerslie  
AUCKLAND

Postal Address: PO Box 125029  
St Heliers  
AUCKLAND

Telephone: 64 09 5793326

Fax: 64 09 5797308

Email: [david@sumnerschist.co.nz](mailto:david@sumnerschist.co.nz)

Website: <http://sumnerschist.co.nz/cladding-stones-and-schist-veneers.html>

# SUMNER Otago - Wanaka NZ Schist Veneer

Product Technical Statement: 102677



differential ultimate limit state (ULS) wind pressure of 2500Pa. Maximum Height Three stories buildings, and chimneys no higher than 10 meters above ground level.

## Company Product Information

### Relationships



New Zealand Made



Codemark BCS-141814-CMNZ



Future Proof Building



BEAL C1108

### Videos

[SUMNER Wanaka Schist - informal seating area.](#)



Date last validated: **30 January 2018**



Date last updated: **30 January 2018**

Disclaimer: The Product Technical Statement (PTS) template is copyright to Construction Information Limited. However the content of this PTS is the responsibility of the product manufacturer/supplier. Refer to the miproducts Terms and Conditions