Solatube Daylighting Systems Product Technical Statement: 102367



Solatube Daylighting Systems provide pure, clear, natural light for any interior space. View miproducts listing



Level of assurance needed to demonstrate NZ Building Code Compliance

Supporting documentation should include technical information by manufacturer and either an independent assessment or reference to an industry-based scheme





Solatube confirms that this minimum level of assurance has been met or exceeded by the following: **BRANZ Appraisal**



The following information has been provided by Solatube demonstrating how this product complies with the **Building Product Information Requirements**.

Technical Statement

Product Class

CLASS 1

Product Description

Solatube Daylight Systems and Roof Penetrations are for use on domestic and commercial buildings, providing a roof penetration system allowing natural light or ventilation to the interior. The system is supplied as a kit providing a tubular roof to ceiling light channel or ventilation duct and a roof flashing system matching the roof type.

Scope of use

Solatube Daylight Systems and Roof Penetrations are for use on domestic and commercial buildings within the following scope

- the scope limitations of E2/AS1, Paragraph 1.1 with respect to building height and maximum floor plan
- · with building structures designed and constructed to meet the requirements of the NZ Building Code
- with roof cladding types and profiles specified in E2/AS1 and
- · for use on flat or nominally flat roofs making use of membrane use systems, and
- situated in NZS 3604 Wind Zones, up to and including 'Very High'

Installs of Solatube Daylighting Systems and Roof Penetrations must only be carried out by HomeTech Certified Installers.

New Zealand Building Code (NZBC)

The product will, if employed in accordance with the supplier's installation and maintenance requirements, assist with meeting the following provisions of the building code:

- Clause B2 Durability: Performance B2.3.1
 - 15 years. Solatube Daylight Systems and Roof Penetrations meet this requirement. Solatube Daylight Systems and Roof Penetrations installations will remain effective with a serviceable life in excess of 15 years, provided they are installed following the instructions of HomeTech Ltd and this Appraisal
- Clause E2 External moisture: Performance E2.3.1, E2.3.2 Solatube Daylight Systems and Roof Penetrations meet these requirement. The Solatube Daylight Systems and Roof Penetrations, when installed in accordance with this Appraisal and the Technical Literature, will prevent the penetration of moisture that could cause undue dampness or damage to building elements.
- Clause F2 Hazardous building materials: Performance F2.3.1 Solatube Daylight Systems and Roof Penetrations meet this requirement.
- Clause G4 Ventilation: Performance G4.3.3 Solatube Daylight Systems and Roof Penetrations, when installed as a ventilation duct, will contribute to meeting these requirements. When a Solatube Daylight System and Roof Penetration is installed and used as a ventilation duct, incorporating a fan, the ventilation system must satisfy the mechanical ventilation requirements of NZBC Acceptable Solution
- Clause G7 Natural light: Performance G7.3.1, G7.3.2 Solatube Daylight Systems and Roof Penetrations will contribute to meeting these requirements. The Solatube Daylight Systems and Roof Penetrations can assist in meeting the NZBC requirements for provision of sufficient natural light to building interiors



masterspec partner

Company Contact Details SOLATUBE Solatube Brand: Just Life Group Company Physical Hugo Johnston Drive Address: Auckland Postal Hugo Johnston Drive Address Auckland Telephone: 64 0800 466383 hello@justlife.co.nz Email: Website: http://www.solatube.co.nz

Solatube Daylighting Systems Product Technical Statement: 102367



• Clause H1 Energy efficiency: Performance H1.3.1 Solatube Daylight Systems and Roof Penetrations will contribute to meeting this requirement. The polycarbonate light diffusion units mounted on the ceiling with a thermal insulation panel gives an R-value of 0.48 and without it gives an R-value of 0.35, thus satisfying the higher skylight R value requirement of 0.34 m²K/W.

Notes

B2.3.1(b) - 15 years.

G4.4.3(a), (b), and (c) - Solatube Daylight Systems and Roof Penetrations when installed as a ventilation duct will contribute to meeting these requirements.

H1.3.1(a) Solatube Daylight Systems and Roof Penetrations will contribute to meeting these requirements.

Evidence 25+ years of supply and installation in the NZ market.

The product meets the requirements set out in the following documents, or relevant parts of cited standards within the documents:

Solatube Daylight Systems and Roof Penetrations light capture domes have been tested to AS4285 and have demonstrated adequate resistance to concentrated loads

Supporting Evidence

The product has and can make available the following additional evidence to support the above



BRANZ Appraisal

665

Use in Service History

Installation of Solatube's date back to 1985 in the NZ market.

Product Criteria

Design requirements

Product specification and incorporation of a Solatube Daylighting Device into the building design shall be carried out by a designer/architect/engineer or building professional who:

- Is qualified to design the buildings covered under the 'Scope' of use of this product.
- · Has ready access to the technical specifications including installation details and standards referenced in the BRANZ Appraisal No. 665 where the design limitations are outlined for the scope of this PTS.

Installation requirements

Solatube Daylighting Systems are installed by the nationwide wide network of certified installation consultants

- 10 year warranty on Product
- 10 year warranty on Installation by a Certified Installation Consultant
- · Tray flashing required for Ministry of Education projects
- Tray flashing may be required for roof pitch below 10 degrees

Maintenance requirements

- · Minimal maintenance is needed for the Solatube Daylighting Systems. It is a sealed unit so should not require cleaning inside
- · Ten year warranty on parts and labour as long as the product is maintained or serviced by a Solatube certified installation consultant.
- Combined mechanical ventilation 5 year warranty on fan.
- The installation warranty is void if re-flashed or serviced by any independent contractor who is not a certified installation consultant
- · Replacement diffusers available

Warrantees

- · Ten year warranty on parts and installation as long as the product is maintained or serviced by a Solatube certified installation consultant.
- Combined mechanical ventilation 5 year warranty on fan.
- The installation warranty is void if re-flashed or serviced by any independent contractor who is not a certified installation consultant.

Company Product Information

Environmental

- · Solatube has been installed into the Living Building Challenge Tuhoi project with a Declare label.
- · Eliminates the need for electric lighting during daylight hours
- · Combines natural lighting with mechanical ventilation for bathrooms and laundries to ensure extraction of unwanted moist air

Solatube Daylighting Systems Product Technical Statement: 102367



• Complies with International LEED Certification and a member of NZ Green Building Council Click link: http://solatube.com/commercial/leed-info

Relationships



Member of New Zealand Green Building Council

Building Product Information Requirements

Manufacturer

Legal Trading Name: Solatube Australia

Importer

Legal Trading Name: Just Life Group

Business Email: hello@justlife.co.nz

Company Website:

https://justlifegroup.co.nz/

Contact Number/s: +64 0800-466383 0800 466383

Product Identifier

SOLATUBE DAYLIGHT SYSTEMS AND ROOF PENETRATIONS ARE FOR USE ON DOMESTIC AND COMMERCIALBUILDINGS, PROVIDING A ROOF PENETRATION SYSTEM ALLOWING NATURAL LIGHT OR VENTILATION TO THE INTERIOR. THE SYSTEM IS SUPPLIED AS A KIT PROVIDING A TUBULAR ROOF TO CEILING LIGHT CHANNEL OR VENTILATION DUCTAND A ROOF FLASHING SYSTEM MATCHING THE ROOF TYPE.

Warnings

This product has no warnings associated with it.



Date last validated: 11 December 2023



Date last updated: 11 December 2023

Disclaimer: The Product Technical Statement (PTS) template is copyright to Construction Information Limited. However the content of this PTS is the responsibility of the product manufacturer/supplier. Refer to the miproducts Terms and Conditions