

Specialized Construction Products Ltd

EZpanel AAC Panel Cladding System

Product Technical Statement: 101753



Lightweight autoclaved aerated concrete panel and plaster system

[View miproducts listing](#)



Level of assurance needed to demonstrate NZ Building Code Compliance

Supporting documentation should include technical information by manufacturer and either an independent assessment or reference to an industry-based scheme



Specialized Construction Products Ltd confirms that this minimum level of assurance has been met or exceeded by the following:

BRANZ Appraisal

[649](#)



masterspec partner

Company Contact Details



Company:	Specialized Construction Products A Division of Dulux
Physical Address:	79 Porana Road Glenfield NORTH SHORE CITY
Postal Address:	79 Porana Road Glenfield NORTH SHORE CITY
Telephone:	64 09 4144499
Email:	scot@specialized.co.nz
Website:	www.specialized.co.nz

Technical Statement

Scope of use

The EZpanel Cavity System is suitable as an external cladding system:

- within the scope limitations of NZBC E2/AS1, Paragraph 1.1; and
- with a risk score of 0-20, calculated in accordance with E2/AS1, Table 2; and
- in NZS 3604 Wind Zones up to and including "Extra High".

The EZpanel Cavity System is also suitable for weathertightness and structural wind loading when used for timber and steel framed buildings subject to specific design up to a design differential ULS wind pressure of 2.5 kPa.

The EZpanel Cavity System must only be installed on vertical surfaces (except for tops of parapets, sills and balustrades, which must have a minimum 10° slope and be waterproofed in accordance with the Technical Literature).

Joinery must meet the requirements of NZS 4211 for the relevant Building Wind Zone or be specifically designed for use in specifically designed buildings.

New Zealand Building Code (NZBC)

The product will, if employed in accordance with the supplier's installation and maintenance requirements, assist with meeting the following provisions of the building code:

- **Clause B1 Structure:** Performance B1.3.1, B1.3.2, B1.3.3, B1.3.4
- **Clause B2 Durability:** Performance B2.3.1(b), B2.3.1(c), B2.3.2
- **Clause E2 External moisture:** Performance E2.3.2
- **Clause F2 Hazardous building materials:** Performance F2.3.1

Notes

B1.3.3 The EZpanel Cavity System meets the requirements for loads arising from (a) self-weight, (f) earthquake, (h) wind, (j) impact loads likely to be encountered in normal residential use, and (q) time dependent effects including creep and shrinkage.

B2.3.1(b) 15 years for the cladding system and plaster finish and (c) 5 years for the exterior paint system

Supporting Evidence

The product has and can make available the following additional evidence to support the above statements:



BRANZ Appraisal

[649](#)

Product Criteria

Design requirements

- Timber framing must comply with NZS 3604 for buildings or parts of buildings within the scope limitations of NZS 3604. Buildings or parts of buildings outside the scope of NZS 3604 must be to a specific design in accordance with NZS 3603 and AS/NZS 1170.
- For steel framing the minimum framing specification is 'C' section studs and nogs of overall section size 75mm web and 32mm flange. Steel thickness must be a minimum of 0.75mm
- All external walls of buildings must have barriers to airflow in the form of interior linings with all joints stopped for wind zones up to and including Very High. Unlined gables and walls must incorporate a rigid sheathing or an air barrier which meets the requirements of NZBC Acceptable Solution E2/AS1, Table 23.

Specialized Construction Products Ltd

EZpanel AAC Panel Cladding System

Product Technical Statement: 101753



See the [EZpanel Specification document](#) for full design requirements

Installation requirements

Installation of components and accessories supplied by Specialized Construction Products Ltd, its certified distributors and certified plasterers must be carried out only by Specialized Construction Products Ltd certified plasterers.

See the [EZpanel specification document](#) for full installation requirements

Maintenance requirements

Regular maintenance is essential to ensure the performance requirements of the NZBC are continually met and to ensure the maximum serviceability of the system. Regular cleaning (at least annually) of the paint coating is required to remove grime, dirt and organic growth and to maximise the life and appearance of the coating. Grime may be removed by brushing with a soft brush, warm water and detergent.

Paint systems must be recoated at approximately 5-8 yearly intervals in accordance with the paint manufacturer's instructions. Annual inspections must be made to ensure that all aspects of the cladding system, including the coating system, plasters, flashings and any sealed joints remain in a weatherproof condition. Any cracks, damaged areas or areas showing signs of deterioration which could allow water ingress must be repaired immediately. The EZpanel Cavity System must be repaired in accordance with the instructions of Specialized Construction Products Ltd.

Company Product Information

Environmental

AAC's high resource efficiency gives it low environmental impact in all phases of its life cycle, from processing of raw materials to the disposal of AAC waste on site during construction. In the manufacturing process, no pollutants or toxic by-products are produced.

Relationships



New Zealand Made

Videos

[EZpanel video](#)



Date last validated: 07 July 2020



Date last updated: 07 July 2020

Disclaimer: The Product Technical Statement (PTS) template is copyright to Construction Information Limited. However the content of this PTS is the responsibility of the product manufacturer/supplier. Refer to the miproducts Terms and Conditions