

# VELUX GGU roof window - white EVERFINISH

Product Technical Statement: 103483



Manual opening (centre hung/pivoting) roof window in white EVERFINISH with ventilation flap

[View miproducts listing](#)



## Level of assurance needed to demonstrate NZ Building Code Compliance

Supporting documentation should include self-assessment and technical information by manufacturer



VELUX confirms that this minimum level of assurance has been met or exceeded by the following:

CodeMark

[CM - 1009](#)

BRANZ Appraisal

[969](#)

VELUX

[Technical Data](#)



## Technical Statement

### Product Description

GGU manual opening roof windows are available in 7 sizes. Suitable for installation within the range from 15° to 90°. GGU Roof Windows is centre-pivoting and consists of the following integrated components – an interior condensation drainage gasket, wooden frame and sash encased in white polyurethane. Exterior maintenance-free aluminium cladding/counter flashing, ASA corner keys, and an insulating thermal pane. Insulating glass unit constructed of a stainless steel spacer with "warm edge" technology, with glazing of internal laminated glass, Argon filled cavity, low E3 coating applied to upper side of internal laminated glass pane. Proprietary VELUX KMG100K electric motor with rainsensor can be fitted to automate the roof window. Used in conjunction with KLC 500 control unit.

### Scope of use

Suitable for all roofs with a pitch between 15-90 degrees, used in conjunction with VELUX proprietary flashings or custom-made flashings in accordance with the latest version of the New Zealand Roofing Code of practice.

### New Zealand Building Code (NZBC)

The product will, if employed in accordance with the supplier's installation and maintenance requirements, assist with meeting the following provisions of the building code:

- **Clause B2 Durability:** Performance B2.3.1, B2.3.2  
Product has CodeMark certification. (BRANZ CM-1009)
- **Clause E2 External moisture:** Performance E2.3.1, E2.3.2, E2.3.7  
Product has CodeMark certification. (BRANZ CM-1009)
- **Clause G4 Ventilation:** Performance G4.3.1, G4.3.3  
Product has CodeMark certification. (BRANZ CM-1009)
- **Clause G7 Natural light:** Performance G7.3.1, G7.3.2  
Product has CodeMark certification. (BRANZ CM-1009)
- **Clause H1 Energy efficiency :** Performance H1.3.1, H1.3.2E, H1.3.3  
Product has CodeMark certification. (BRANZ CM-1009)

### Notes

B2/AS1 Durability - AS 4285 - VELUX Skylights satisfy the durability requirements specified for Non-structural Roof Cladding elements and External Window/Door Joinery.

C3 Protection from Fire - AS 1530 - VELUX Skylights have been classified as "non-combustible" according to AS 1530 test methods.

E2 External Moisture - AS 4285 - VELUX Skylights have passed tests for weather tightness, concentrated load, non-cyclonic and cyclonic wind pressures .

F2 Hazardous Building Materials - NZS 4233: Part 4, AS/NZS 4666 - VELUX Skylights comply with requirements for sloped Insulating Glass Units. G4/AS1 Natural Ventilation (1.2, 2.1) - VELUX Opening Skylights can be used to meet the

G4 Natural Ventilation requirements.

G7 Natural Light - VELUX Skylights can be used to meet the G7 Natural Light requirements.

## masterspec partner

### Company Contact Details



### Skylights

Company:	VELUX New Zealand Limited
Physical Address:	62b Princes Street Onehunga AUCKLAND
Postal Address:	62b Princes Street Onehunga AUCKLAND
Telephone:	64 09 6344126
Email:	<a href="mailto:info@velux.co.nz">info@velux.co.nz</a>
Website:	<a href="http://www.velux.co.nz">http://www.velux.co.nz</a>

# VELUX GGU roof window - white EVERFINISH

Product Technical Statement: 103483



H1 Energy Efficiency - NZS 4218 - VELUX Skylights exceed the minimum R-value requirements for skylights in all climate zones.

## Evidence

The product meets the requirements set out in the following documents, or relevant parts of cited standards within the documents:

- B2/AS1 Durability - AS 4285 - VELUX Skylights satisfy the durability requirements specified for Non-structural Roof Cladding elements and External Window/Door Joinery. VELUX Skylights have passed tests for weather tightness, concentrated load, non-cyclonic and cyclonic wind pressures according to Australian Skylight Standard AS4285 test methods.
- C3 Protection from Fire - AS 1530 - VELUX Skylights have been classified as "non-combustible" according to AS 1530 test methods.
- E2 External Moisture - AS 4285 - VELUX Skylights have passed tests for weather tightness, concentrated load, non-cyclonic and cyclonic wind pressures according to Australian Skylight Standard AS4285 test methods.
- F2 Hazardous Building Materials - NZS 4233: Part 4, AS/NZS 4666 - VELUX Skylights comply with requirements for sloped Insulating Glass Units.
- G4/AS1 Natural Ventilation (1.2, 2.1) - VELUX Opening Skylights can be used to meet the G4 Natural Ventilation requirements.
- G7 Natural Light - VELUX Skylights can be used to meet the G7 Natural Light requirements.
- H1 Energy Efficiency - NZS 4218 - VELUX Skylights exceed the minimum R-value requirements for skylights in all climate zones.
- Evidence: 30+ years of historical use in New Zealand

## Supporting Evidence

The product has and can make available the following additional evidence to support the above statements:



CodeMark  
[CM - 1009](#)  
BRANZ Appraisal  
[969](#)  
VELUX  
[Technical Data](#)

## Use in Service History

40+ years use in New Zealand

## Product Criteria

### Design requirements

GGU Roof Windows are modular manual opening Roof Windows intended for roof pitches between 15 and 90 degrees. They are available in standard sizes only. The IGU glazing unit has argon gas fill and Low E3 applied to the inside surface of the outer pane. The IGU unit meets the requirements of NZBC F2

GGU Roof Windows have been tested for impact but are not intended to be part of a trafficable roof surface.

GGU Roof Windows do not have a fire rating.

### Installation requirements

Install GGU roof window in accordance with instructions supplied with GGU roof window and local building code requirements. [PG\\_452953-2013-03-GGL-GGU\\_V22.indd \(azureedge.net\)](#) Align skylight with the trim opening, free of warp or twist, maintaining dimensional tolerances. Attach skylight to the trim-out frame with screws furnished by manufacturer. Coordinate attachment and seal of perimeter air and vapor barrier material. Weathertightness to be achieved by using either VELUX proprietary flashings installed in accordance with supplied installation instructions, or custom-made flashings made in accordance with the latest version of NZ Roofing Code of Practice.

### Maintenance requirements

For maintenance requirements refer to <http://https://www.velux.co.nz/service-and-warranty/maintenance>. Exterior surfaces must be cleaned with clean water at least once a year, subject to the environmental conditions present.

### Warrantees

For warrantees refer to <http://https://www.velux.co.nz/service-and-warranty/maintenance>.

## Company Product Information

### Quality Assurance



ISO 9001 (Quality Management)

# VELUX GGU roof window - white EVERFINISH

Product Technical Statement: 103483



Date last validated: **03 November 2023**



Date last updated: **03 November 2023**

Disclaimer: The Product Technical Statement (PTS) template is copyright to Construction Information Limited. However the content of this PTS is the responsibility of the product manufacturer/supplier. Refer to the miproducts Terms and Conditions