Viking Roofspec CertainTeed Asphalt Shingles

Product Technical Statement: 102460

miproducts

Lightweight roofing system comprising stylish asphalt shingles installed over a plywood substrate.

View miproducts listing



Level of assurance needed to demonstrate NZ Building Code Compliance

Supporting documentation should include technical information by manufacturer and either a BRANZ or independent Appraisal or CodeMark





Viking Roofspec confirms that this minimum level of assurance has been met or exceeded by the following: BRANZ Appraisal

276 (2018)

Technical Statement

Scope of use

Viking CertainTeed asphalt roofing shingles have been appraised as a roof cladding for buildings within the following scope:

- Viking CertainTeed asphalt roofing shingles have been appraised as a roof cladding for buildings within the following scope:
- The scope limitations of NZBC Acceptable Solution E2/AS1 Paragraph 1.1, with regard to floor plan area and building height; and,
- Constructed with timber roof framing and plywood sheathing complying with the NZBC: and.
- Where the roof slope is 9 degrees or greater; and, Situated in NZS 3604 Wind Zones up to and including High, or Extra High for the Landmark series, Highland Slate and Independence shingles only.

New Zealand Building Code (NZBC)

The product will, if employed in accordance with the supplier's installation and maintenance requirements, assist with meeting the following provisions of the building code:

- Clause B1 Structure: Performance B1.3.1, B1.3.2, B1.3.3, B1.3.4
- Clause B2 Durability: Performance B2.3.1, B2.3.1(b)
- Clause E2 External moisture: Performance E2.3.1, E2.3.2, E2.3.6
- Clause F2 Hazardous building materials: Performance F2.3.1

Notes

CertainTeed meets B 1.3.3 (a), (b), (c), (g), (h), (j) and (q).

Supporting Evidence

The product has and can make available the following additional evidence to support the above statements:



BRANZ Appraisal 276 (2018)

Product Criteria

Design requirements

Product specification and incorporation of Viking CertainTeed asphalt shingles into the building design shall be carried out by a designer/architect/engineer or a building professional who:

- Is qualified to design the buildings covered under the 'Scope' of use of this
 product.
- Has ready access to the technical specifications including installation details and standards referenced in the BRANZ Appraisal No. 276 (2018) where the design limitations are outlined for the scope of this PTS.

The CertainTeed system incorporates a range of accessories including vents, underlay and flashings to name a few. <u>Click here for a comprehensive list of accessories</u>.

Installation requirements





masterspec partner

Company Contact Details

CertainTeed Shingles

Brand: Viking Roofspec

Company: Viking Roofspec

Physical 80 Alexander Crescent

Address: Otara

AUCKLAND

Address:

Postal PO Box 14541

Panmure AUCKLAND

Telephone: 64 09 2729709

Fax: 64 0800 729788

Email: <u>info@vikingroofspec.co.nz</u>

Website: <a href="http://www.vikingroofspec.co.nz/catalog/product/Viking-product/

 $\underline{\text{certainteed-asphalt-roofing-shingles}}$

Viking Roofspec CertainTeed Asphalt Shingles

Product Technical Statement: 102460

miproducts

- · Installation shall be carried out by a Viking trained installer.
- Installation shall be undertaken in accordance with all relevant technical information related to the selected installation method, including information contained within the BRANZ Appraisal No. 276 (2018).
- Long term properties of the material may be affected by contact with petroleumbased products such as oils, greases and solvents.

Maintenance requirements

- Little maintenance should be required apart from the removal of lichen, moss and organic growth that may become established and the removal of accumulations of the stone granules in spouting.
- Annual inspections must be made to ensure that all aspects of the roof cladding, including the pre-finished coating, the flashings and any joints remain in a weatherproof condition. Any damaged areas or areas showing signs of deterioration which would allow water ingress must be repaired immediately.
- A water-based chemical treatment recommended by Viking Roofspec as being suitable for use with bitumen-based products must be used for the removal of organic material. Petroleum-based solvents or cleaners must not be used.

Warrantees

The Viking CertainTeed asphalt shingles system is backed by product warranties ranging from 20-50 years (depending on the profile). For specific projects, CertainTeed may be eligible to be covered by Viking's Full System Warranty. This warranty covers the product and installation in one document, for a 20-year period.

Company Product Information

Environmental

- By utilising what would otherwise be waste materials, such as slag residue from oil refining, the manufacturing process of CertainTeed shingles reduces land fill waste and greenhouse gas emissions.
- At the end of their serviceable life, shingles can be overlaid (special conditions apply), avoiding the dumping of inorganic materials.
- Lighter colours in the CertainTeed range; many of which carry US CoolStar energy ratings, reduce the energy required to cool a building.
- CertainTeed asphalt shingles meet the AS/NZS 4020 testing of products for use in contact with drinking water standard, so they can be used for the collection of drinking water.

Quality Assurance



ISO 9001 (Quality Management)

Relationships



Member of New Zealand Green Building Council



BRANZ 276

Videos

CertainTeed Asphalt Shingles Installation and Vent



Date last validated: 07 July 2020



Date last updated: 07 July 2020

Disclaimer: The Product Technical Statement (PTS) template is copyright to Construction Information Limited. However the content of this PTS is the responsibility of the product manufacturer/supplier. Refer to the miproducts Terms and Conditions