

Waterproofing Systems NZ Ltd bituFLAME Roof & Deck Membrane

Product Technical Statement: 100227



is a high performance modified bitumen membrane providing superior waterproofing protection.

[View miproducts listing](#)



Level of assurance needed to demonstrate NZ Building Code Compliance

Supporting documentation should include technical information by manufacturer and either a BRANZ or independent Appraisal or CodeMark



Waterproofing Systems NZ Ltd confirms that this minimum level of assurance has been met or exceeded by the following:

BRANZ Appraisal

[404](#)

Technical Statement

Product Description

bituFLAME is an APP modified bitumen membrane reinforced with 180 - 200 gsm non-woven polyester fabric. bituFLAME has good flexibility at both high and low temperatures

Scope of use

The bituFLAME torch-on membrane system is used to provide waterproofing protection on commercial, industrial, apartments, residential roofs and balconies with an extensive accessory range which is fully compatible providing the best waterproofing protection system available.

bituFLAME torchon membrane system complies with the NZBC as an alternative solution BRANZ appraisal number (404) for use on roofs, decks and for potable water supplies.

One of the advantages of bituFLAME is the comprehensive range of specialist membrane systems: for roofing, tanking, planter boxes, green roofs, ballast roofs and re-roofing old bitumen roof membranes.

bituFLAME is BRANZ appraised for timber raft and tileJAK systems.

New Zealand Building Code (NZBC)

The product will, if employed in accordance with the supplier's installation and maintenance requirements, assist with meeting the following provisions of the building code:

- **Clause B2 Durability:** Performance B2.3.1(b)
- **Clause E2 External moisture:** Performance E2.3.1, E2.3.2
- **Clause F2 Hazardous building materials:** Performance F2.3.1

Notes

Durability statement: bituFLAME has been specified in the market for more than 20 years therefore surpassing its in-service 20 year warrantable life.

Evidence

The product meets the requirements set out in the following documents, or relevant parts of cited standards within the documents:

bituflame meets the following

B2 Durability Performance B2.3.1(b)

E2 External Moisture E2.3.1 and E2.3.2

F2 Hazardous Building Materials F2.3.1

Potable water run-off approved (refer to BRANZ Appraisal 404)

Supporting Evidence

The product has and can make available the following additional evidence to support the above statements:



BRANZ Appraisal

[404](#)

Use in Service History

Waterproofing Systems NZ Ltd bituFLAME has a in service history in New Zealand since 2008, previously polyFLAME first introduced to the Market 23 years ago.\



Company Contact Details

BITUFLAME

TORCH-ON MEMBRANE

Brand: Waterproofing Systems NZ Ltd

Company: Waterproofing Systems NZ Ltd

Physical Address: Malvern Road
Onehunga
Auckland

Postal Address: Malvern Road
Onehunga
Auckland

Telephone: 64 09 5791460

Fax: 64 09 5791461

Email: info@waterproofing.co.nz

Website: <http://www.waterproofing.co.nz>

Waterproofing Systems NZ Ltd bituFLAME Roof & Deck Membrane

Product Technical Statement: 100227



Product Criteria

Design requirements

Plywood and concrete substrates to be clean and fully dry/cured.

Plywood: Construction Plywood grade H3.2 CCA treated kiln dried 17mm thick for roofs, 19mm thick for decks.

Concrete: smooth surface finish to be either U2 wood float or U3 steel trowel to NZ 3114.

Specified falls:

Roofs - 2° slope (1:30)

Decks - 1.5° slope (1:40)

Gutters - 1° slope (1:100)

Installation requirements

Refer the Waterproofing Systems installation guidelines and specifications.

Only installed by licenced LBP registered Waterproofing Systems NZ Ltd applicators.

Quality Control checksheets must be completed for each job and kept as a record of evidence to ensure the installation meets WPSNZ specification.

The bituFLAME system should be installed in dry conditions. The substrate must have a maximum moisture content of 20% for plywood and 75% RH for concrete at the time of laying.

Substrate falls for the installation are correct.

Dropper outlets and scuppers are installed to specification.

Primer is applied at the correct application rate.

Extruded bitumen fillets are installed to specification.

Installation of bituFLAME membrane system.

Maintenance requirements

Refer to the Care & Maintenance instructions available on our website and are attached to the Warranty document.

Warrantees

When installed to specification and subject to normal environmental conditions and use, the bituFLAME membrane system will exceed 20 year period when properly maintained.

A material warranty is issued on receipt of Quality Control Checksheet/s and warranty application.

15 Year Material Warranty for a single layer installation (insitu concrete only)

20 Year Material Warranty for a 2 layer installation

Company Product Information

Environmental

Clause F2 Hazardous Building Materials: Performance F2.3.1 bituFLAME Roof & Deck membranes meet this requirement and will not present a health hazard to people.



Date last validated: 07 July 2020



Date last updated: 07 July 2020

Disclaimer: The Product Technical Statement (PTS) template is copyright to Construction Information Limited. However the content of this PTS is the responsibility of the product manufacturer/supplier. Refer to the miproducts Terms and Conditions